



BE-GF-15WP

GFCI Receptacle — 15A Tamper & Weather Resistant
Production Specification | Belle Electric Part #: BE-GF-15WP

GENERAL SPECIFICATIONS		CERTIFICATIONS	GFCI WORKING STATUS		TR	
Part #:	BE-GF-15WP	- UL/CUL Listed - NOM Certified - CSA Certified - UL Listed E504391 - UL@943 Class A GFCIs & UL@498 - Complies to NEC® - Self-Test: UL@943 5th Ed./CSA 22.2 MATERIAL - Face & Body: Thermoplastic 0.8mm phosphorus bronze contacts 1.2mm galvanized steel bracket - Silver alloy contacts (30 silver layer) - Smart chip MCU — moisture protected - Flammability: UL-94 V2 Rating DIMENSIONS Std Plate: 4.53 in H × 2.75 in W (115×70mm) Screwless: 4.53 in H × 2.75 in W (115×70mm) Line Wiring: Brass screw (Black/Hot) Neutral Wire: Silver screw (White) Ground: Green screw	Green Light GFCI OK. Cyclic self-test every 15 min. Red Blinking GFCI self-testing in progress. Red Light ON Service life reached — replace unit. LED Off Tripped. Press RESET. Check circuit.	WR		
Product:	GFCI Receptacle		APPLICATIONS		TR WR  15A GFCI Outlet Self-Test Color: White WH 15A,125V,60Hz. Back & Side Wire. Tamper & Weather-Resistant (NEC 406.8). NEMA 5-15R. UL/CUL LISTED Certifications: - UL/CUL Listed - NOM Certified - CSA Certified	
UPC:	8747003240300		Residential:			
Amperage:	15A		- Bathrooms, Kitchens, Basements - Garages, Laundry rooms, Wet locations			
Voltage:	125V		Commercial:			
Frequency:	60Hz		- Classrooms & Laboratories - Airports & Commercial offices - Restaurants, Hotels & Public bathrooms - Any wet or damp location			
NEMA:	5-15R		AVAILABLE COLORS			
Features:	Tamper-Resistant, Weather-Resistant		White WH Ivory IV Almond AL Grey GR Black BK Brown BR			
Wiring:	Back & Side Wire		UL/CUL LISTED			
Poles/Wires:	2-pole / 3-wire		Certifications:			
Contact Mat.:	Brass		- UL/CUL Listed - NOM Certified - CSA Certified			
Torque:	16 lbf-inch		15A,125V,60Hz. Back & Side Wire. Tamper & Weather-Resistant (NEC 406.8). NEMA 5-15R.			
Circuit Type:	GFCI Self-Test					
Device Type:	Receptacle					
Weight:	122g/0.269 lb					
Length:	1.56 in					
Height:	4.07 in					
Width:	1.71 in					
ELECTRICAL						
Trip Level:	4~6 mA					
Trip Time:	< 025 Sec					
Max Interrupt:	10,000 A					
Working V:	102~132V					
Rating V:	125V					
Op. Temp:	-35■ to 66■					
Max Humidity:	95%					

All information current at time of publication. Belle Electric reserves the right to update product information without notice. | Spec Sheet Rev. 2025