



BE-PC-CLN Series

Low VOC PVC Pipe Cleaner — Clear

Spec Sheet | Belle Electric Part Numbers | Low VOC | Ground Freight Only — Flammable (Class 3)

PRODUCT DESCRIPTION	PHYSICAL PROPERTIES	
Low VOC Pipe Cleaner — a clear blend of solvents formulated to clean and prepare the surfaces of PVC, uPVC, CPVC, ABS, and Styrene pipe and fittings prior to cementing. Removes surface dirt, grease, and contaminants to ensure a strong, reliable solvent-cemented joint.	Color: Clear	
	Body: Regular	
	Specific Gravity: 0.794	
	Shelf Life: 3 years (unopened)	
APPLICATION	Max VOC (SCAQMD): 20 g/L (SCAQMD Rule 1171)	Low VOC Pipe Cleaner — Clear
- PVC and uPVC pipe and fittings - CPVC pipe and fittings - ABS pipe and fittings - Styrene pipe and fittings - Apply with dauber or clean dry cloth before cementing - Always follow instructions on the label	VOC Rating: Low VOC	
	TEMPERATURES	
	Application: -10°F to 110°F (-23°C to 43°C)	
	Storage: -10°F to 110°F (-23°C to 43°C)	
QUALITY ASSURANCE	CERTIFICATIONS	PART NUMBER GUIDE
Every batch is carefully checked and monitored to assure consistently high quality standards. Records of every batch are kept. All ingredients are purchased from approved suppliers.	✓ ASTM F402-18 Compliant	Format: BE-PC-CLN[Size]
	✓ SCAQMD Rule 1171	CLN = Cleaner / Clear
	✓ Compatible: PVC / uPVC	
	✓ Compatible: CPVC	
	✓ Compatible: ABS & Styrene	

AVAILABILITY & PACKAGING — All Sizes

Size	BE Part #	Fluid oz	Liters	Units / Case	Case Wt. (lb)	Case Wt. (kg)	Cu Ft / Case	Cu M / Case	Cases / Pallet
1/4 Pint (QP)	BE-PC-CLN1QP	4	0.12	24	9.5	4.32	0.260	0.007	145
1/2 Pint (HP)	BE-PC-CLN1HP	8	0.24	24	16	7.27	0.420	0.012	90
Pint (PT)	BE-PC-CLN1P	16	0.47	12	15.5	7.05	0.404	0.011	88
Quart (QT)	BE-PC-CLN1Q	32	0.95	12	28	12.73	0.762	0.022	56
Gallon (GA)	BE-PC-CLN1G	128	3.78	6	54	24.55	1.221	0.035	27

Pint and Quart cans are supplied with dauber inside cap. 1/4 pt and 1/2 pt supplied with plain cap. Gallon sizes supplied with plain cap only.

SAFETY PRECAUTIONS	SHIPPING & TRANSPORTATION
Ensure adequate ventilation — avoid vapor build-up (flash fire hazard). Avoid contact with eyes, skin, and clothing. Use safety glasses and gloves. Inhalation: If breathing is difficult, vacate to fresh air. If breathing problems persist, seek immediate medical attention. Eyes: Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention. Ingestion: Give 1-2 glasses of water immediately. Call physician, hospital, or poison control. DO NOT INDUCE VOMITING. WARNING: Can expose you to vinyl chloride, a carcinogen. See www.P65Warnings.ca.gov	Under 1 liter (1/4 pt – 1/2 pt): Exempt under DOT Limited Quantity Rules. May be shipped as ORM-D Consumer Commodity. Not subject to shipping paper requirements for flammable materials. 1 liter and larger (Pint, Quart, Gallon): Proper Shipping Name: Compound Cleaning Liquid Flammable Class: 3 UN Number: UN 1993 Packing Group: PG II
	GROUND FREIGHT ONLY — Flammable liquid. Cannot ship via air freight (UPS Air, FedEx Air, USPS Priority).

All information current at time of publication. Always follow label instructions and consult the Safety Data Sheet (SDS) before use. Belle Electric reserves the right to update product information without notice. | Spec Sheet Rev. 2025