



BE-PC-CLR Series

Low VOC PVC Conduit Cement — Regular Body / Clear

Spec Sheet | Belle Electric Part Numbers | UL 651 Listed | Ground Freight Only — Flammable (Class 3)

PRODUCT DESCRIPTION	PHYSICAL PROPERTIES	
Low VOC PVC Conduit Cement, Regular Body, Fast-Set. Formulated for conduit applications up to 8" (200 mm) diameter on Schedule 40 PVC/uPVC conduit. Meets ASTM D2564, UL 651, NEMA TC-2, TC-6, and TC-8. Makes consistently leak-proof joints when used as directed.	Color: Clear	
	Body: Regular	
	Set Speed: Fast	
	Specific Gravity: 0.902	
APPLICATION	Shelf Life: 3 years (unopened)	Low VOC Conduit Cement Regular Body / Clear
■ PVC / uPVC conduit up to 8" (200 mm) diameter ■ Schedule 40 conduit and fittings ■ For superior joints use with primer (clear or purple) ■ Never add thinner or additive to cement ■ Never use if stringy or jelly-like in consistency ■ Always follow label instructions	Max VOC (SCAQMD): 414 g/L	
	VOC Rating: Low VOC	
	TEMPERATURES	
	Application: 32°F to 110°F (0°C to 43°C)	
	Storage: 45°F to 110°F (7°C to 43°C)	
QUALITY ASSURANCE	CERTIFICATIONS	PART NUMBER GUIDE Format: BE-PC-CLR[Size] CLR = Clear Regular Body
Every batch is carefully checked and monitored to assure consistently high quality standards. Records of every batch are kept. All ingredients are purchased from approved suppliers.	✓ ASTM D2564	
	✓ UL 651 Listed	
	✓ NEMA TC-2	
	✓ NEMA TC-6	
	✓ NEMA TC-8	

AVAILABILITY & PACKAGING — All Sizes

Size	BE Part #	Fluid oz	Liters	Units / Case	Case Wt. (lb)	Case Wt. (kg)	Cu Ft / Case	Cu M / Case	Cases / Pallet
1/4 Pint (QP)	BE-PC-CLR1QP	4	0.12	24	9.5	4.32	0.260	0.007	145
1/2 Pint (HP)	BE-PC-CLR1HP	8	0.24	24	16	7.27	0.420	0.012	90
Pint (PT)	BE-PC-CLR1P	16	0.47	12	15.5	7.05	0.404	0.011	88
Quart (QT)	BE-PC-CLR1Q	32	0.95	12	28	12.73	0.762	0.022	56
Gallon (GA)	BE-PC-CLR1G	128	3.78	6	54	24.55	1.221	0.035	27

1/4 pt, 1/2 pt, Pint, and Quart cans are supplied with dauber inside cap. Gallon sizes supplied with plain cap only.

SAFETY PRECAUTIONS	SHIPPING & TRANSPORTATION
Ensure adequate ventilation — avoid vapor build-up (flash fire hazard). Avoid contact with eyes, skin, and clothing. Use safety glasses and gloves.	Under 1 liter (1/4 pt – 1/2 pt): Exempt under DOT Limited Quantity Rules. May be shipped as ORM-D Consumer Commodity. Not subject to shipping paper requirements for flammable materials.
Inhalation: If breathing is difficult, vacate to fresh air. If breathing problems persist, seek immediate medical attention.	1 liter and larger (Pint, Quart, Gallon):
Eyes: Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention.	Proper Shipping Name: Adhesive
Ingestion: Give 1-2 glasses of water immediately. Call physician, hospital, or poison control. DO NOT INDUCE VOMITING.	Flammable Class: 3
■ WARNING: Can expose you to vinyl chloride, a carcinogen. See www.P65Warnings.ca.gov	UN Number: UN 1133
	Packing Group: PG II
	■ GROUND FREIGHT ONLY — Flammable liquid. Cannot ship via air freight (UPS Air, FedEx Air, USPS Priority).

All information current at time of publication. Always follow label instructions and consult the Safety Data Sheet (SDS) before use. Belle Electric reserves the right to update product information without notice. | Spec Sheet Rev. 2025