



BE-PC-ENT Series

ENT Low VOC PVC/uPVC Cement — Medium Body / Blue

Spec Sheet | Belle Electric Part Numbers | NSF Certified | ENT / SMURF Pipe | Ground Freight Only — Flammable (Class 3)

PRODUCT DESCRIPTION	PHYSICAL PROPERTIES
ENT Low VOC PVC/uPVC Cement — medium body, fast-set, high strength blue cement for all PVC electrical conduit and ENT ("SMURF") pipe. Interference fit through 6" (160 mm) diameter. Meets ASTM D2564.	Color: Blue Body: Medium Bodied Set Speed: Fast Specific Gravity: 0.954 Shelf Life: 3 years (unopened) Max VOC (SCAQMD): 510 g/L (Rule 1168/316A) VOC Rating: Low VOC
APPLICATION	TEMPERATURES
■ All PVC electrical conduit — interference fit through 6" (160 mm) ■ ENT (Electrical Non-Metallic Tubing) — commonly known as "SMURF" pipe ■ Any non-pressure PVC with interference fit ■ For superior joints use with primer (clear or purple) ■ Never add thinner or additive — always follow label	Application: 32°F to 110°F (0°C to 43°C) Storage: 45°F to 110°F (7°C to 43°C)
QUALITY ASSURANCE	CERTIFICATIONS
Every batch is carefully checked and monitored to assure consistently high quality standards. Records of every batch are kept. All ingredients are purchased from approved suppliers.	✓ ASTM D2564 Certified ✓ NSF International & IAPMO Listed ✓ Uniform Plumbing Code (UPC) Seal ✓ UL 651 / UL 651A Compliant ✓ Schedule 40 & 80 — up to 6" (160 mm) diameter



ENT Low VOC PVC Cement Medium Body / Blue

PART NUMBER GUIDE

Format: BE-PC-ENT[Size]

ENT = ENT Cement / Blue

AVAILABILITY & PACKAGING — All Sizes

Size	BE Part #	Fluid oz	Liters	Units / Case	Case Wt. (lb)	Case Wt. (kg)	Cu Ft / Case	Cu M / Case	Cases / Pallet
1/4 Pint (QP)	BE-PC-ENT1QP	4	0.12	24	9.5	4.32	0.260	0.007	145
1/2 Pint (HP)	BE-PC-ENT1HP	8	0.24	24	16	7.27	0.420	0.012	90
Pint (PT)	BE-PC-ENT1P	16	0.47	12	15.5	7.05	0.404	0.011	88
Quart (QT)	BE-PC-ENT1Q	32	0.95	12	28	12.73	0.762	0.022	56
Gallon (GA)	BE-PC-ENT1G	128	3.78	6	54	24.55	1.221	0.035	27

1/4 pt, 1/2 pt, Pint, and Quart cans are supplied with dauber inside cap. Gallon sizes supplied with plain cap only.

SAFETY PRECAUTIONS	SHIPPING & TRANSPORTATION
Ensure adequate ventilation — avoid vapor build-up (flash fire hazard). Avoid contact with eyes, skin, and clothing. Use safety glasses and gloves. Inhalation: If breathing is difficult, vacate to fresh air. If breathing problems persist, seek immediate medical attention. Eyes: Flush eyes thoroughly with water for 15 minutes. Get immediate medical attention. Ingestion: Give 1-2 glasses of water immediately. Call physician, hospital, or poison control. DO NOT INDUCE VOMITING. ■ WARNING: Can expose you to vinyl chloride, a carcinogen. See www.P65Warnings.ca.gov	Under 1 liter (1/4 pt – 1/2 pt): Exempt under DOT Limited Quantity Rules. May be shipped as ORM-D Consumer Commodity. Not subject to shipping paper requirements for flammable materials. 1 liter and larger (Pint, Quart, Gallon): Proper Shipping Name: Adhesive Flammable Class: 3 UN Number: UN 1133 Packing Group: PG II ■ GROUND FREIGHT ONLY — Flammable liquid. Cannot ship via air freight (UPS Air, FedEx Air, USPS Priority).

All information current at time of publication. Always follow label instructions and consult the Safety Data Sheet (SDS) before use. Belle Electric reserves the right to update product information without notice. | Spec Sheet Rev. 2025